

# Addressing Energy Responsibility in Particle Accelerators: Insights from the KITTEN Research Platform

**Prof. Dr.-Ing. Giovanni De Carne**, Prof. Dr. Anke-Susanne Müller, Dr. Erik Bründermann, Dr. Julian Gethmann  
Dr. Falastine Abusaif, M.Sc. Mashid Zadeh  
Karlsruhe Institute of Technology - 26/09/2024




# What is our starting point?

## Base Load

Around 40% of the base load of 7GWh is related to labs and beamlines. 8% for the insertion devices.

Around 40% goes for the building power and the cooling system.

The storage ring and pumps take only 8% of the base load.



- Ring
- Pumps
- Cooling Central
- Building services
- IDs
- Beamlines
- Labs
- Labs cooling





# KIT TEN

KIT test center for energy efficiency & grid stability  
in large-scale research infrastructures

A joint venture between the accelerator **KARA** and the test-field **Energy Lab 2.0** to improve the energy use and power quality in large research infrastructures.




## KARA Digital Twin

- Power supply quality improvements
- Integration of energy storage systems
- DC connectivity


## Energy Data Dashboard

- Energy management for sustainability purposes
- Energy costs analysis
- Human-Machine-Interface improvements

# Fast communication infrastructure for Real Time Digital Twins




# Measurement System Placement



## Measurement points


- Injector PS + microtron dipole
- CATACT + CLIC wiggler
- Di-, Quadri-, and Sextuple magnets
- RF system (only partially)





# Initial Results

- First data transmission between KARA and Energy Lab 2.0 successful
- With UDP protocol we transmit voltage and current data at 1 kHz
- Good for steady state analysis but not for dynamics
- Next steps:
  - Employing EtherCAT that enables the data transmission up to 10 kHz
  - Lay a dedicated fiber optic connection




# Why a Digital Twin is important?

## Performing **Power Hardware In the Loop** testing

### Advantages



- No need of real hardware during testing novel controllers or technologies
- Safer environment for “risky testing” (e.g., faults)
- No need for waiting accelerator shut-down → reduction in integration time






# Power consumption per day at KARA in 2023

## Power generation with photovoltaics





# Consumption Research Building incl. Laboratories, Beamlines, Accelerator (here no beam in accelerator)

- Photovoltaics indicates sunlight
- Partially/delayed correlated with outside air temperature (typically some hysteresis – temperature highest typically around 16:00 to 17:00).
- Power consumption related to sunlight heating the walls and roof of the research building with the accelerator, laboratories and beamlines inside.



# Photovoltaics to Smooth Consumption Curve

## Peak Net Consumption (clouds cover photovoltaics)







# Cooling System Power Dependency on Beam Energy

- We found a correlation between the required cooling power and the beam energy
- There is a cooling power variation from 90 kW in off-line weeks vs. 280 kW during beam operation
- Now studying the dependency on the external temperature → data campaign to be finished in the next weeks

## Beam Energy (GeV)




## Cooling plants (kW)




June 2024

Gesamtleistung KARA



Dipoles

Einzelmessungen



# KITTEN – Upgrade Testing Possibility at KARA

Energy measures targeting an energy-independent accelerator


- Photovoltaic (Q4 2024)
  - Doubling installed power (240 kWp → 500 kWp)
- Geothermal Energy System (Q1 2025)
  - 1MW Thermal power, COP=3, passive thermal exchanger
- Battery Energy Storage Systems (Q1 2025)
  - 2x500kW, 2x871=1742kWh → 3.5 hours full power operation
  - Dynamic, 20ms reaction time, suitable for power quality purpose and islanding
- Targeting a **50% / 70%** energy dependency reduction from the public grid



# Research Facility 2.0

## FACTS

- Horizon Europe Project (2024 – 2027)
- 10 partners, 5.6 M€ Budget
  - 6 accelerators, 4 SMEs
- 4 Demonstrators
  - Efficient Solid State Amplifiers @ALBA, HZB
  - Efficient Permanent Magnets @MAX IV, HZB
  - Phasor Measurement Units @CERN
  - Flexible Data Centers @DESY



## Concrete improvement measures for current and future accelerators

**Prof. Dr.-Ing. Giovanni De Carne**  
Director of the Institute for Technical Physics  
Head of Power Hardware In the Loop lab

**Karlsruhe Institute of Technology**  
Institute for Technical Physics (ITEP)

Phone: +49 721 608-25924  
Email: [giovanni.carne@kit.edu](mailto:giovanni.carne@kit.edu)



For further information  
and to follow our  
project progress visit  
[www.rf20.eu](http://www.rf20.eu)



and our Social Media accounts:  RF2.0 Project  @rf20\_project



This project has received funding from the European Union's Horizon Europe research and innovation programme under grant agreement No. 101131850 and from the Swiss State Secretariat for Education, Research and Innovation (SERI).



Schweizerische Eidgenossenschaft  
Confédération suisse  
Confederazione Svizzera  
Confederaziun svizra

Swiss Confederation

Federal Department of Economic Affairs,  
Education and Research EAER  
**State Secretariat for Education,  
Research and Innovation SERI**

Prof.Dr.-Ing. Giovanni De Carne